307 DIMENSIONAL REQUIREMENTS (#31)

307.1 SCHEDULE OF DIMENSIONAL REQUIREMENTS (#57)

All parcels of land, structures and uses shall meet or exceed the following minimum dimensional requirements. Non-conforming parcels of land cannot be created unless otherwise indicated in this ordinance. Letters adjacent to some dimensional requirements refer to notes at the end of the schedule which contain additional requirements.

	RURAL	LDR	MDR-1	MDR-2	HDR	HDR-2	СВ	GB	IND	IND-2	OR	PB	DD
1. Minimum		,		ı			1			1.			
Lot Area													
(square feet)													
Off-lot	60,000	40,000	15,000	7,000	7,000	15,000	2,000	40,000	30,000	40,000	7,000	20,000	1,500
sewer and water													
On-lot	70,000	50,000	30,000	30,000	N/A	N/A	N/A	N/A	80,000	80,000	N/A	N/A	N/A
sewer, public													
water													
On-lot sewer	120,000	60,000	40,000	40,000	N/A	N/A	N/A	N/A	200,000	200,000	N/A	N/A	N/A
and water													
2. Minimum													
area/Family													
(square feet)		I	T		T	T	1		I .		T	1 .	
Off-lot	60,000	40,000	15,000-	7,000	3,900	15,000	_	N/A	N/A	N/A	3,900	N/A	V
sewer and water			С			-H	P						
On-lot	70,000	50,000	30,000	30,000	N/A	N/A	P	N/A	N/A	N/A	N/A	N/A	N/A
sewer, public													
water	100000		40.000	40.000	37/1	27/1		37/1	27/1	27/1	27/1	27/1	27/1
On-lot sewer	120,000	60,000	40,000	40,000	N/A	N/A	P	N/A	N/A	N/A	N/A	N/A	N/A
and water													
3. Minimum													
Lot Frontage													
(feet)	200	150	100	7.5	50	100	25 D	200	150	200	100 T	150	25
Off-lot	200	150	100	75	50	100	25-P	200	150	200	100-J	150	25
Sewer and water On-lot	200	150	125	125	N/A	N/A	N/A	N/A	200	200	N/A	N/A	N/A
sewer, public	200	130	123	123	IN/A	IN/A	IN/A	N/A	200	200	IN/A	IN/A	N/A
water													
On-lot sewer	200	150	150	150	N/A	N/A	N/A	N/A	400	400	N/A	N/A	N/A
and water	200	130	130	130	IN/A	1 \ / A	1N/A	IN/A	400	400	1N/A	1N/A	IN/A
4. Minimum	40-A	A-40-	30-A	30-A	A	30-A	20-A	50-	20-E	30-E	A	50-	0,
Depth Frontage	10 71	A	30 71	30 71	11	30 11	20 11	F,E	20 L	30 L	11	F,E	
(feet)		11						1,2				1,2	
(#25)													
5. Minimum	25'	20'-B	15'	15'	5,	15'	5'-	20'	G'	20'	15'K	20' S	0'-T
Width Side	Q-25'	Q-20'	Q-5'	Q-5'	Q-5'	Q-5'	L,P	Q-5'	Q-20'	Q-20'	Q-5'	Q-20'	
Yard (feet) (#9)							Q-5'						
6. Minimum	35'	35'	25'	25'	30'	25'-I	20'	30'	20'	20'	25'	30' S	0'-T
Width Rear	R-35'	R-35'	R-5'	R-5'	R-5'	R-5'	R-5'	R-5'	R-20'	R-20'	R-5'	R-15'	
Yard (feet) (#9)													1
	I	·	·	I		1		L	l	<u> </u>	L	1	L

7. Maximum Building or Structure Coverage Percentage (#21)	15	33 1/3	33 1/3	33 1/3	33 1/3	33 1/3	50	50	50	50	50	50	100-T
8. Maximum Building Height (feet)	35-	35-	35-	35-	35-	65-	65-	N/A-	N/A-	N/A-	35-	90-	65-
	M,N	M,N	M,N	M,N	M,N	N,P	N,P	N	N	N	M,N	M,N	T,U

- A. The lesser of: 1- the defined setback, or 2- the average setback of the six (6) adjacent structures (three (3) on each side) except as otherwise provided in Section 436.6 of this Land Use Code. (#25)
- B. Buildings or structures more than twenty (20) feet from ground level in height shall be set back one (1) foot additional for each additional foot in height.
- C. 7,000 for publicly assisted housing for the elderly, subject to the Site Plan Review.
- D. Plus 700 gross floor area above grade of principle structure per family.
- E. References may be had to Section 436.6 of this Land Use Code. (#25)
- F. 75 feet on Wilson and State Streets and 25 feet along Dirigo Drive. (#25)
- G. A total of forty (40) feet with one (1) a minimum of ten (10) feet.
- H. Additional dwelling units in the same building: add 3,000 square feet per unit plus 1,000 square feet per separate bedroom.
- I. Plus five (5) feet for each family over one (1).
- J. Fifty (50) feet for residential use.
- K. Five (5) feet for residential use.
- L. May be reduced to zero with Firewall Separation.
- M. Spires, belfries, cupolas, antennae, chimneys or other appurtenances usually required to be placed above the roof level and not intended for human occupancy shall not exceed forty-five (45) feet above average ground level unless they are set back from front, rear and side lot lines one (1) additional foot to the required setback for each foot of excess height.
- N. Free standing structures not intended for human occupancy which are permitted uses and subject to Site Plan Review may exceed the stated height limitation, provided that for each additional linear foot in height, there is one (1) linear foot setback from adjacent property and street lines added to the required setback.
- O. The Code Enforcement Officer may authorize a height in excess of sixty-five (65) feet, provided that for each additional linear foot in height, there is one (1) linear foot setback from adjacent property and street lines added to that required setback.
- P. Lot and Yard Requirements for Dwellings:
 - 1. Minimum Lot Area (sq. ft.) A lot equal to the area needed for the dwelling units, driveways, parking spaces, accessory buildings, minimum yard requirements, maximum lot coverage, and six hundred (600) square feet of open space for the first dwelling unit and an additional two hundred (200) square feet of open space for each additional dwelling unit.
 - 2. Minimum Lot Frontage

50 feet.

3. Minimum Depth Front Yard

20 feet.

Minimum Width Side Yard
 Minimum Depth Rear Yard
 Maximum Building or Structure coverage
 %.

- Q. Side Line Setbacks for detached accessory structures. (Garages, sheds, swimming pools, free standing decks, gazebos, etc.)
- R. Rear Line Setbacks for detached accessory structures. (Garages, sheds, swimming pools, free standing decks, gazebos, etc.)
- S. For planned group developments may be reduced to zero with fire separation, as provided under the codes and ordinances of the City of Brewer. (#9)
- T. Requires fire separation between buildings and all buildings above two stories are required to be sprinkled. (#31)
- U. Buildings must be a minimum of two stories in height. (#31)
- V. All dwelling units must contain a minimum of 500 square feet each. (#31)